

customized highest state highest
PRECISION OF THE ART QUALITY QUALITY
VALVOLE APR
UNLOADER VALVES - REGULATEURS - REGULADORES

Valvole regolazione pressione, attacco con viti cave pompe serie: WM-TM

Unloader valves with banjo connections for pumps WM-TM series

Régulateurs de pression avec vis de fixation pour pompes série WM-TM

Válvulas de regulación de presión, conexión con tornillos de fijación para bombas WM-TM

Temperatura max: 60°C - 140°F

Max temperature: 60°C - 140°F

Température max: 60°C - 140°F

Temperatura máx: 60°C - 140°F

APR 30



CODICE CODE (**)	COLOR	MODELLO MODEL	PRESSIONE MAX MAX PRESSURE		PORTATA FLOW		Attacco pompa Port size	Entrata Inlet	Uscita Outlet	PESO WEIGHT	
			BAR	PSI	l/min	GPM	BSP	BSP		Kg	lbs
05.8720.97.3	Blue	APR 30	210	3000	21	5.5	3/8 1/2	1/2 - M	3/8 BSP - M	0.86	1.9
05.8723.97.3	Blue	APR 30	210	3000	21	5.5	3/8 1/2	1/2 - M	22x1.5 - M	0.90	2.0

APR.I 30



CODICE CODE (**)	COLOR	MODELLO MODEL	PRESSIONE MAX MAX PRESSURE		PORTATA FLOW		Attacco pompa Port size	Entrata Inlet	Uscita Outlet	PESO WEIGHT	
			BAR	PSI	l/min	GPM	BSP	BSP		Kg	lbs
05.8719.97.3	Blue	APR.I 30 Fixed injector 1.6 (*)	210	3000	15	4	3/8 1/2	1/2 - M	3/8 BSP - M	0.90	2.0
05.8722.97.3	Blue	APR.I 30 Fixed injector 1.6 (*)	210	3000	15	4	3/8 1/2	1/2 - M	22x1.5 - M	0.95	2.1
05.8718.97.3	Blue	APR.I 30 Adjust injector 1.6 (*)	210	3000	15	4	3/8 1/2	1/2 - M	3/8 BSP - M	0.90	2.0
05.8721.97.3	Blue	APR.I 30 Adjust injector 1.6 (*)	210	3000	15	4	3/8 1/2	1/2 - M	22x1.5 - M	0.95	2.1

Valvole regolazione pressione, attacco con viti cave pompe serie: WBX

Unloader valves with banjo connections for pumps WBX series

Régulateurs de pression avec vis de fixation pour pompes série WBX

Válvulas de regulación de presión, conexión con tornillos de fijación para bombas WBX

Temperatura max: 60°C - 140°F

Max temperature: 60°C - 140°F

Température max: 60°C - 140°F

Temperatura máx: 60°C - 140°F

APR 35



CODICE CODE (**)	COLOR	MODELLO MODEL	PRESSIONE MAX MAX PRESSURE		PORTATA FLOW		Attacco pompa Port size	Entrata Inlet	Uscita Outlet	PESO WEIGHT	
			BAR	PSI	l/min	GPM	BSP	BSP		Kg	lbs
05.8751.97.3	Green	APR 35	240	3500	21	5.5	3/8 3/8	1/2 - M	3/8 BSP - M	1.10	2.4
05.8754.97.3	Green	APR 35	240	3500	21	5.5	3/8 3/8	1/2 - M	22x1.5 - M	1.15	2.5

APR.I 35



CODICE CODE (**)	COLOR	MODELLO MODEL	PRESSIONE MAX MAX PRESSURE		PORTATA FLOW		Attacco pompa Port size	Entrata Inlet	Uscita Outlet	PESO WEIGHT	
			BAR	PSI	l/min	GPM	BSP	BSP		Kg	lbs
05.8752.97.3	Green	APR.I 35 Fixed injector 1.6 (*)	240	3500	15	4	3/8 3/8	1/2 - M	3/8 BSP - M	1.15	2.5
05.8755.97.3	Green	APR.I 35 Fixed injector 1.6 (*)	240	3500	15	4	3/8 3/8	1/2 - M	22x1.5 - M	1.20	2.65
05.8753.97.3	Green	APR.I 35 Adjust injector 1.6 (*)	240	3500	15	4	3/8 3/8	1/2 - M	3/8 BSP - M	1.15	2.5
05.8759.97.3	Green	APR.I 35 Adjust injector 1.6 (*)	240	3500	15	4	3/8 3/8	1/2 - M	22x1.5 - M	1.20	2.65

(*) Optional ugello eiettore 1.8 - 2.1 - 2.3 -Optional injector nozzle 1.8 - 2.1 - 2.3

Optionnel buse injecteur 1.8 - 2.1 - 2.3 -Opción boquilla eyectora 1.8 - 2.1 - 2.3

(**) Versione speciale per umidificazione: stesso codice con ultima cifra "B" in sostituzione del "3"

Special version for misting/fogging: the same part nr. with the last figure "B" that replaces "3"

Version spéciale pour brumisation: la même référence avec la dernière lettre "B" qui remplace "3"

Versión especial para humidificación: el mismo código con la última cifra "B" que reemplaza el "3"